



## ProCore

Article Number 145223, 145225, 145227, 145229

### Description:

Versatile professional masking tape made from FSC certified paper for indoor use. Has excellent adhesive ability, while still being easy to remove. Sticks for up to 7 days, but should be kept out of direct sunlight. ProCore is resistant against all solvent- and waterbased paints.

### Use:

Clean the surface, that the tape should stick to, so it is grease- and dustfree.  
ProCore is ideal for most materials, and can easily be used on bent profiles and irregular surfaces.  
We recommend doing an adhesive test prior to the actual work.

### Productdata:

Backing material	Saturated semi-crepe paper 59 g/m <sup>2</sup>
Adhesive	Natural rubber
Total Thickness	136 $\mu$ (+ / - 10%)
Adhesion to steel	280 g/cm
Flexibility	7%
Temperature resistance	up to +80 °C (30 min)
Pullforce	3,5 kg / cm
Removal Time	7 days, indoors

Art. Nr	EAN	Description	Width	Length	Colli
145223	5707985452231	ProCore tape 19mm x 50m	19 mm	50 m	48
145225	5707985452255	ProCore tape 25mm x 50m	25 mm	50 m	72
145227	5707985452279	ProCore tape 38mm x 50m	38 mm	50 m	48
145229	5707985452293	ProCore tape 50mm x 50m	50 mm	50 m	36



If you need additional information, we are at your disposal.